

A19 & A21 - LED Omnidirectional



A19
E26



A21
E26



A19
GU24



A21
GU24

6/9/
11/15
watts

replaces
40-100W
incan.

GU24
or E26
base

300°
beam spread

features

- Direct replacement for 40, 60, 75, 100W incandescent A lamps
- 300° Omni beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Smooth, clean outside housing
- Compatible with a wide array of dimmers
- Comfortable diffused light
- Instant-On with no warm up, unlike CFLs
- Available in 2700K, 3000K, and 4000K
- Shatter resistant for reduced risk of injury and breakage



performance

- 6W replaces 40W incandescent
- 9W replaces 60W incandescent
- 11W replaces 75W incandescent
- 15W replaces 100W incandescent
- 120V @ 60Hz
- Standard series 80+ CRI for enhanced color and lighting uniformity from lamp to lamp
- ANSI construction compliant
- Suitable for damp locations
- 25,000 hour rated life for ENERGY STAR® Approved lamps*
- 50,000 hour design life**
- Not for use in enclosed fixtures

applications

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare

* Early initial qualification for ENERGY STAR allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass ENERGY STAR requirements, manufacturers may increase the lifetime of a product as dictated by ENERGY STAR guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.

** Design life is based on engineering testing and probability analysis



A19 & A21 - LED Omnidirectional

dimensions



ordering information

A19 & A21 Omnidirectional - Medium E26 Base

Litespan Part #	Order Code	Watts	Lumens	CCT	CRI	Beam Angle	MOL	Life Hours**	Replaces Incandescent	ENERGY STAR
LED10WA19/300/827K-DIM-G4	90091	9.8W	800	2700K	80+	300°	4.41"	25,000	60W A19	★
LED10WA19/300/830K-DIM-G4	90089	9.8W	800	3000K	80+	300°	4.41"	25,000	60W A19	★
LED10WA19/300/840K-DIM-G4	90087	9.8W	800	4000K	80+	300°	4.41"	25,000	60W A19	★
LED12WA19/300/827K-DIM-G4	90082	12W	1,100	2700K	80+	300°	4.41"	25,000	75W A19	★
LED12WA19/300/830K-DIM-G4†	90079	12W	1,100	3000K	80+	300°	4.41"	25,000	75W A19	★
LED12WA19/300/840K-DIM-G4†	90077	12W	1,100	4000K	80+	300°	4.41"	25,000	75W A19	★
LED17WA21/300/827K-DIM-G4	90053	17W	1,600	2700K	80+	300°	5.12"	25,000	100W A21	★
LED17WA21/300/830K-DIM-G4	90051	17W	1,600	3000K	80+	300°	5.12"	25,000	100W A21	★
LED17WA21/300/840K-DIM-G4	90049	17W	1,600	4000K	80+	300°	5.12"	25,000	100W A21	★
LED6WA19/300/827K-DIM-G5*	08952	6W	470	2700K	80+	300°	4.41"	25,000	40W A19	★
LED6WA19/300/830K-DIM-G5*	08953	6W	470	3000K	80+	300°	4.41"	25,000	40W A19	★
LED6WA19/300/840K-DIM-G5*	08954	6W	470	4000K	80+	300°	4.41"	25,000	40W A19	★
LED9WA19/300/827K-DIM-G5*	08917	9W	800	2700K	80+	300°	4.41"	25,000	60W A19	★
LED9WA19/300/830K-DIM-G5*	08918	9W	800	3000K	80+	300°	4.41"	25,000	60W A19	★
LED9WA19/300/840K-DIM-G5*	08919	9W	800	4000K	80+	300°	4.41"	25,000	60W A19	★
LED11WA19/300/827K-DIM-G5*	08914	11W	1,100	2700K	80+	300°	4.53"	25,000	75W A19	★
LED11WA19/300/830K-DIM-G5*	08915	11W	1,100	3000K	80+	300°	4.53"	25,000	75W A19	★
LED11WA19/300/840K-DIM-G5*	08916	11W	1,100	4000K	80+	300°	4.53"	25,000	75W A19	★
LED15WA21/300/827K-DIM-G5*	08920	15W	1,600	2700K	80+	300°	5.24"	25,000	100W A21	★
LED15WA21/300/830K-DIM-G5*	08921	15W	1,600	3000K	80+	300°	5.24"	25,000	100W A21	★
LED15WA21/300/840K-DIM-G5*	08922	15W	1,600	4000K	80+	300°	5.24"	25,000	100W A21	★

*Available Q4 2015

†Canada only

★ENERGY STAR® Approved


** 25,000 hour ENERGY STAR® rated life. 50,000 hour design life. See note on obverse.



A19 & A21 - LED Omnidirectional

ordering information

A19 & A21 Omnidirectional - GU24 Base

Litespan Part #	Order Code	Watts	Lumens	CCT	CRI	Beam Angle	MOL	Life Hours**	Replaces Incandescent	
LED10WA19/300/827K-GU24-DIM-G4	90090	9.8W	800	2700K	80+	300°	4.41"	25,000	60W A19	★
LED10WA19/300/830K-GU24-DIM-G4	90088	9.8W	800	3000K	80+	300°	4.41"	25,000	60W A19	★
LED10WA19/300/840K-GU24-DIM-G4†	90086	9.8W	800	4000K	80+	300°	4.41"	25,000	60W A19	★
LED12WA19/300/827K-GU24-DIM-G4	90081	12W	1,100	2700K	80+	300°	4.41"	25,000	75W A19	★
LED12WA19/300/830K-GU24-DIM-G4	90079	12W	1,100	3000K	80+	300°	4.41"	25,000	75W A19	★
LED17WA21/300/830K-GU24-DIM-G4	90050	17W	1,600	3000K	80+	300°	5.12"	25,000	100W A21	★
LED17WA21/300/840K-GU24-DIM-G4	90048	17W	1,600	4000K	80+	300°	5.12"	25,000	100W A21	★
LED9WA19/300/827K-GU24-DIM-G5*	08923	9W	800	2700K	80+	300°	4.41"	25,000	60W A19	★
LED9WA19/300/830K-GU24-DIM-G5*	08924	9W	800	3000K	80+	300°	4.41"	25,000	60W A19	★
LED9WA19/300/840K-GU24-DIM-G5*	08925	9W	800	4000K	80+	300°	4.41"	25,000	60W A19	★
LED11WA19/300/827K-GU24-DIM-G5*	08926	11W	1,100	2700K	80+	300°	4.41"	25,000	75W A19	★
LED11WA19/300/830K-GU24-DIM-G5*	08927	11W	1,100	3000K	80+	300°	4.41"	25,000	75W A19	★
LED11WA19/300/840K-GU24-DIM-G5*	08928	11W	1,100	4000K	80+	300°	4.41"	25,000	75W A19	★
LED15WA21/300/827K-GU24-DIM-G5*	08929	15W	1,600	2700K	80+	300°	5.24"	25,000	100W A21	★
LED15WA21/300/830K-GU24-DIM-G5*	08930	15W	1,600	3000K	80+	300°	5.24"	25,000	100W A21	★
LED15WA21/300/840K-GU24-DIM-G5*	08931	15W	1,600	4000K	80+	300°	5.24"	25,000	100W A21	★

*Available Q4 2015

†Canada only

★ENERGY STAR® Approved

** 25,000 hour ENERGY STAR® rated life. 50,000 hour design life. See note on observe.

watch > like > follow



selection. solutions. simplicity. eiko.com

23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335