

LED C35 CANDLE BULB DATA SHEET



FEATURES

High quality replacement for 35W incandescent candle bulbs. Consuming Only 5W and save more than 80% energy costs over conventional lamps.

- Pure aluminum heatsink, cold-forging aluminum fins;
- Heat conduction coefficient is 1.5 times higher than the Aluminum Profile
- Instant-on with no warm up time
- Free of harmful mercury, environment friendly
- Excellent dimmers compatible ability and dimming performance
- 2700K/3000K/4000K/5000K CCT options available
- ETL/cETL/CE approved
- RoHS compliant

*Dimmable 100%-10% when using triac dimmers.

Compatible dimmers include:

Lutron SCL-I53P, DVCL-I53P, CTCL-I53P among others

INSTALLATION

- Do not use where exposed to weather, IP20.

LED C35 BULBS

| | |
|----------------------|----------------------------------|
| Item No.: | CL5G-EI2 |
| Power: | 5W |
| Input Voltage: | AC110-130V (50/60Hz) |
| Power Factor: | >0.9 |
| LED Type: | COB LED (Chips On Board) |
| Color Temperature: | 2700K/3000K/4000K/5000K |
| CRI: | RA83 (RA90+ Optional) |
| Lumen Flux: | 450-500lm |
| Beam angle: | 360 Degree |
| Dimmable: | Yes |
| Lifespan: | 40,000H |
| Working Temperature: | -20~40°C |
| Socket: | E12/E14 |
| Material: | Pure Aluminum + PC Lens |
| Size: | Ø37*107mm (D1.45xH4.21 inch) |
| Package information: | 100pcs/ctn, 31*30*37cm, 9kgs/ctn |

DIMENSIONS

