


5.5"x4' WRAPAROUND LIGHT, 48 watt 4000 Lumen, ETL/cETL & Energy Star

## Specifications

Model#	<b>BL-WR-486-48W-2CCT</b>
Description	<b>5.5"x4' WRAPAROUND LIGHT</b>
Power	<b>48W</b>
Voltage Input	<b>120Vac,60HZ</b>
Lumen output	<b>5520lm</b>
CCT	<b>2CCT :4000K,5000K</b>
CRI	<b>Ra&gt;80</b>
Housing	<b>Steel base white powder coating</b>
Application	<b>Indoor Only</b>
Driver	<b>UL certified</b>
Lens	<b>PC</b>
Operating Temp.	<b>-25 °C ~55 °C</b>
IP Rating	<b>IP20</b>
Certificates	<b>ETL/cETL,Energy Star</b>
warranty	<b>3 years</b>
Dimmable	<b>YES 0-10 V</b>
Product Dimension	<b>48"L x 5.5"W x 1.6" H (1220mm x 140 x 52 mm)</b>



CCT Tunable



•Link options:  
Cable connect 1' and Flush connect included

Dim + Dim -




up to 8pcs together

Build in Dimmable line in 5 pin cable connect

## Order Information


Item Number	Description	Power	Voltage Input	Driver	CCT	Lumen Output	Certificates
BL-WR-486-48W-2CCT	5.5"x4' WRAPAROUND LIGHT	48W	120Vac	UL Certified	4000K & 5000K	5520lm	ETL/cETL , Energy Star

## Lux Chart



Height	Average Lux (lx)	Light range (dia.)
1M	525.5	258.3cm
2M	131.4	516.6cm
3M	58.4	774.9cm
4M	32.8	1033.2cm
5M	21.0	1291.5cm

## Photometrics



**LM79**  
**LM80**

