

# REVELATION

by UTTERMOST

## ASSEMBLY INSTRUCTIONS

### STYLE#: R21300

#### Carefully unpack all lamp parts from the carton.

1. Take the lamp carefully out of the Carton, and place it on a flat surface.
2. Be sure the power to the installation point is power off. This lamp must be installed on reinforced **outlet box**.
3. Decide the height of **Chain** you like. Then thread **Quick Link #1** into **Loop #1** on the top of the lamp body and **Quick Link #2** into **Loop #2** on the **Canopy**. Hand tighten until snug. Lock the **Chain** on the other side the same way.
4. Secure the Plastic Connectors to the ceiling according to the position of Hole #3 and Hole #4 on both side of Universal Bar.
5. Pull the wire from the **Canopy** and then the center hole in the **Universal Bar**. The power supply wire consists of three wires, one black wire, one white wire and one green ground wire.
6. Connect the wires as shown :
  - A. Connect the House Ground Wire to the Fixture Ground Wire.
  - B. Connect the House White or Ribbed Wire to the Fixture Supply Wire (White or Ribbed Side).
  - C. Connect the House Black/Red Wire to the Fixture Supply Wire (Black or Smooth Side).
  - D. Wrap each connected wire with Wire Nut and carefully stuff all of the connected wires into the Outlet Box.
7. Thread the **Screw** onto **Hole #1** downside on both side of the **Universal Bar**. Then Thread the other two **Screws** onto **Hole #3** and **Hole #4** upside separately and secure them into the **Plastic Connector**.
8. Thread another two **Screws** through **Hole #2** upside on both side of the **Universal Bar**, and secure them into the **Outlet Box**.
9. Secure the **Screw** out form **Hole #1** with **Hex Nut #1**. Then Secure the **Mounting Ball** onto the **Screw** too. Secure the **Hex Nut** and **Mounting Ball** on the other side the same way.
10. The **Socket wire** can be wound as you like, or you also can wind them as follows.
  - A. Wind Socket #1 clockwise half circle;
  - B. Wind Socket #2 counterclockwise one circle;
  - C. Wind Socket #3 clockwise half circle;
  - D. Wind Socket #4 counterclockwise one circle;
  - E. Wind Socket #5 clockwise half circle.
  - F. Wind Socket #6 one circle counterclockwise;
  - G. Wind Socket #7 clockwise half circle;
  - H. Wind Socket #8 counterclockwise one circle;
  - I. Wind Socket #9 clockwise half circle.
11. Install correct **bulbs**(Not Included) to the **socket** referring to fixture markings and/or labels for maximum wattage.

