

STYLE# **R21335**

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Carefully unpack all lamp parts from carton. We suggest a licensed electrician for all fixture installations.

- 1. Take the lamp carefully out of the Carton, and place on a flat surface.
- 2. Be sure power to the installation point is OFF. Follow the steps below for assembly.
- 3. Adjust the length of wire needed for your installation, remove excess. Determine the number of Rods to be assembled to the Fixture Body as needed for your hanging height. Pull the Supply Wire with Ground Wire through the selected Rods and Loop and Quick Link. Thread the Rods & connect Nipple. Hand tighten.
- 4. Attach one end of the Quick Link#1 and Loop#1 on the bottom of Canopy, and then attach the other end of the Quick Link#2 onto the Rods. Then turn the Loop#2 same direction with Loop#1.
- **5.**Secure the **Crossbar** to the outlet box with outletbox screws. Tighten until snug.
- **6**. Connect the wire as shown.
 - a. Connect the House Ground Wire to the Fixture Ground Wire, secure with wire nut.
 - **b.**Connect the House White (or Ribbed) Wire to the Fixture Supply Wire (White or Ribbed Side) secure with wire nut.
 - c. Connect the House Black (or Red) Wire to the Fixture Supply Wire (Black or Smooth Side), secure with wire nut.
 - d.Carefully stuff all of the connected wires into the Outlet Box.
- 7. Thread the Finial onto the end of the Screw and hand tighten until snug.
- 8. Place **Glass Shade** instruction as below.(See Figure 2)
- Step 1: Place Glass shade into the Part#1. Make sure the spider on the part#1 hold the Glass shade completely and straightly.
- Step 2: Put down the Part#2 in the Glass shade.
- Step 3: Thread the Part #3 into the Nipple. Hand-tighten until snug.
- Step 4: Assembly Glass Shade is Completed
- 9. Install the correct Edison Bulb(Not Included) into the Socket until snug.

Your installation is completed now. Restore electricity.

