

STYLE#: R22151

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Carefully unpack all lamp parts from the carton.

- 1. Take the lamp carefully out of the Carton, and place it on a flat surface.
- 2. Be sure the power to the installation point is power off.
- 3. Fasten the Cross bar to the outlet box .Secure the Nipple onto the Canopy with Loop #1.
- **4.**Adjust chain length as needed. Thread **Quick Link#1** into **Loop #1** on the Canopy, then **Quick Link#2** into Loop #2 on the **Lamp Body.** Hand tighten until snug.
- 5. The power supply wire consists of three wires, one black wire, one white wire and one silver ground wire.
 - Connect the wires as shown. A. Connect the House Ground Wire to the Fixture Ground Wire.
 - **B.**Connect the House White (or Ribbed) Wire to the Fixture Supply Wire (White or Ribbed Side).
 - C.Connect the House Black (or Red) Wire to the Fixture Supply Wire (Black or Smooth Side).
 - D. Wrap each connected wire with Wire Connector and carefully stuff all of the connected wires into the Outlet Box.
- 6. Install the correct Edison Bulb (Not Included) onto the Socket referring to fixture markings and/or labels for maximum wattage.
- 7. Place Glass shade into the Part#1, then threaded the Part#3 to connect the Part#2 and Glass Shade. Hand tighten until sung.

Your installation is completed now. Restore electricity.

