Holland

Ceiling Mounted • Damp Location Listed PROGRESS LED

Description:

Enjoy nothing but breathtaking design inspiration with the gorgeous ceiling fan. Four simple, yet stunning blades blend style with sustainability as they anchor to a sleek center. An integrated LED light is ready to offer a gentle glow along with the fan's refreshing breeze. With the versatility to be installed in indoor or outdoor locations, this fan will make a design statement in any modern or transitional setting.

Specifications:

- White Opal glass Bowl
- Four simple, yet stunning blades blend style with sustainability as they anchor to a sleek center.
- An integrated LED light is ready to offer a gentle glow along with the fan's refreshing breeze.
- Able to be installed in indoor and outdoor locations.
- Ideal for any living room, great room, or bedroom.
- Perfect for modern and transitional settings.
- Measures 60-inch width by 16-5/8-inch height.
- Uses one LED module that is included (24w max).
- Remote control included.
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.125 in W., 2.19 in ht., 5.125 in depth
- 80 in of wire supplied

P250032-108-30

Performance:

| Number of Modules	1
Input Power	24 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	2,000/83 (LM-82)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
Warranty	Limited Lifetime Warranty
Labels	cULus Damp Location Listed
	Meets California Title 24 JA8-2019
	DC motor

Dimensions:

Diameter: 60 in
Height: 16-5/8 in

White Opal glass Bowl
Width: 7-3/4 in
Height: 2 in

ENERGYGUIDE

Estimated
Yearly Energy Cost
$6

$3 $34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- **Your cost depends on rates and use**
- Energy Use: 21 Watts

Airflow
5,457
Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move
- Airflow Efficiency: 257 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights   ftc.gov/energy

Dimming Notes:

P250032-108-30

P250032-108-30 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron	NTEVL-300
Lutron	DVELV-300P
Lutron	DVCL-253P
iDevices	IDEV009
Lutron	THCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.
Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.