

Project:

Fixture Type:

\_\_\_\_\_

Location: Contact:

### Edwidge

#### Ceiling Mounted • Damp Location Listed PROGRESS LED

# P250062-152-30

#### **Description:**

Edwidge Collection 3-Blade Painted Nickel 52-Inch DC Motor LED Contemporary Ceiling Fan

#### **Specifications:**

- Frosted Acrylic Bowl
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.75 in W., 2.25 in ht., 5.75 in depth
- + 80 in of wire supplied

#### **Performance:**

Number of Modules	1
Input Power	18 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,400
ССТ	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	Limited Lifetime Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016
	DC motor



#### **Dimensions:**

Length: 52 in Diameter: 52 in Height: 13-1/2 in

Frosted Acrylic Bowl Width: 7-1/2 in Height: 2-1/2 in



## Edwidge

Ceiling Mounted • Damp Location Listed PROGRESS LED

#### **Dimming Notes:**

P250062-152-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

#### **Dimming Controls:**

Eaton AAL06
IDevices IDEV009
Leviton 6681
Leviton 6672
Leviton 6674
Lutron NTEVL-300
Lutron DVELV-300P
Lutron DVCL-253P
Lutron AYCL-153P
Lutron SCL-153P
Lutron TGCL-153-PH-WH
Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

## P250062-152-30