

## Trevina II

Ceiling Mounted • Dry Location Listed **PROGRESS LED**

### Description:

This ceiling fan includes an LED light source covered by a white opal shade to help extend your day into the evening. You and your family will relax in your peaceful retreat created by the cool breeze coming from the three-blades rotating overhead. The fixture is coated in a brushed nickel finish to complete the handsome design.

### Specifications:

- White Opal glass Bowl
- You and your family will relax in your peaceful retreat created by the cool breeze coming from the three-blades rotating overhead.
- This ceiling fan includes an LED light source covered by a white opal shade to help extend your day into the evening.
- The fixture is coated in a brushed nickel finish to complete the handsome design.
- Ideal for any bedroom or den.
- Perfect for modern or traditional settings.
- Measures 44-inch width by 15-5/8-inch height.
- Uses one LED module 18w.
- Full dimmable
- Includes wall control for both ceiling fan and light.
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.88 in W., 2.38 in ht., 5.88 in depth
- 80 in of wire supplied

### Performance:

Number of Modules	1
Input Power	18 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1,600/84 (LM-82)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
Warranty	Limited Lifetime Warranty
Labels	UL Dry Location Listed
	Meets California Title 24 JA8-2019
	AC motor

# P2555-0930K



### Dimensions:

Diameter: 44 in  
 Height: 15-5/8 in

White Opal glass Bowl  
 Width: 8 in  
 Height: 2 in

## ENERGYGUIDE

**Estimated  
Yearly Energy Cost**

\$7

\$3 | | | \$34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- **Your cost depends on rates and use**
- Energy Use: 26 Watts

**Airflow**

3,235

Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move.
- Airflow Efficiency: 122 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy

# P2555-0930K

## Dimming Notes:

---

P2555-0930K is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Eaton AAL06

IDevices IDEV009

Leviton 6681

Leviton 6672

Leviton 6674

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron AYCL-153P

Lutron SCL-153P

Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.