

Phase 2.2 LED

Wall mounted • Damp location listed



P300213-009-30

Description:

Phase 2.2 features a thin, acrylic shade framed by architectural accents in Brushed Nickel complete the design. This specially designed 486in. linear bath fixture delivers ambient light to surfaces free of shadows. Ideal for residential, commercial and multi-family applications. An integrated LED source provides energy and cost savings benefits. Can be installed vertically or horizontally.

Specifications:

- Brushed Nickel (-009) (plated)
- Aluminum Construction
- White Acrylic diffuser
- The white acrylic shade provides even illumination
- Square end caps and square decorative arms that extend from the back plate are finished in Brushed Nickel
- The LED light is diffused to create an even glow
- Ideal for residential, commercial and multi-family applications
- Mount horizontally or vertically on the wall in bath and vanity settings
- Measures 48in W x 4-3/4in ht.
- 44w integrated LED, 3,250 delivered lumens 74 lumens/watt, 3000K color temperature, 90+ CRI.
- ETL Safety listed for use in damp locations
- Compatible with many ELV dimmers
- Progress Lighting products are designed for exceptional quality, reliability, and functionality
- Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	44w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	
Lumens/LPW (Delivered)	3250/74 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5-year limited warranty
Labels	cETLus Damp location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

Images:



Dimensions:

Width: 48"
 Depth: 4"
 Height: 4-3/4"
 H/CTR: 2-3/8" (horizontal)

Glass
 Width: 47-1/8"
 Height: 3"



P300213-009-30

Dimming Notes:

is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Lutron DVELV-300P

Lutron Caseta

Leviton 6681

Lutron AYCL-153P

Lutron MAELV-600

Lutron AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.