

## Everlume

 Wall or Ceiling Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Everlume Collection 1-Light Satin White Frosted Glass LED Modern Bath Vanity Linear Panel Light

### Specifications:

- Frosted Polystyrene Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Frame covers a standard 4" recessed outlet box: 9.84 in W., 0.78 in ht., 4.37 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied
- Americans With Disabilities Act (ADA) compliant

### Performance:

Number of Modules	1
Input Power	17 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,386/81 (LM-79)
CCT	3000 K 4000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed Meets California Title 24 JA8-2019

# P300304-028-CS



### Dimensions:

Length: 15-15/16 in  
 Extends: 1.38 in  
 Height: 5 in  
 H/CTR: 2-1/2 in

Frosted Polystyrene Diffuser  
 Width: 0.39 in  
 Height: 4 in

# P300304-028-CS

## Dimming Notes:

---

P300304-028-CS is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Eaton AAL06

Eaton SAL06P

IDevices IDEV009

Leviton 6672

Leviton 6674

Lutron NTEVL-300

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron SCL-153P

Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.