

Project:

Fixture Type:

Location:

Contact:

Barril LED

Wall Mounted • Damp Location Listed PROGRESS LED

ROGRESS

P300408-31M-30

Description:

Barril Collection 24 in. Matte Black Medium Modern Integrated LED Linear Vanity Light

Specifications:

- Diffused Plastic Curved Panel
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" recessed outlet box: 9.84 in W., 4.37 in ht., 0.78 in depth
- + Mounting backplate for outlet box included
- 10 in of wire supplied
- Americans With Disabilities Act (ADA) compliant

Performance:

Input Power	22 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,813/82 (LM-79)
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	Meets California Title 24 JA8-2016



Dimensions:

Width: 24 in Extends: 2-1/4 in Height: 4-11/16 in (glass facing up)



Barril LED

Wall Mounted • Damp Location Listed PROGRESS LED

Photometrics:

ELECTRICAL DATA	P300408-31M-30
Input Voltage	120 V
Input Frequency	60 Hz
THD	<20%
EMI/RFI	FCC Title 47, Part 15, Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	
*See Dimming Notes for more information	

P300408-31M-30



Barril LED

Wall Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

 ${\sf P300408\text{-}31M\text{-}30}$ is designed to be compatible with many ELV/Reverse Phase Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

aton SAL06P
eviton 6681
eviton IPI06-1LZ
eviton 6672
eviton 6674
utron NTEVL-300
utron DVELV-300P
utron DVCL-253P
utron Caseta Wireless
devices IDEV009
utron AYCL-153P
utron SCL-153P
utron TGCL-153-PH-WH
utron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P300408-31M-30