

Project:		
Fixture Type:		
Location:		
Contact:		

ONE-LIGHT FLUSH MOUNT

Ceiling mounted • Damp location listed PROGRESS LED

Description:

A 12" domed, linen finish glass diffuser is discreetly supported from Brushed Nickel metal fittings and encloses an LED light source. 1,000 lumens 90+ CRI, 3000K.

P350055-009-30

Images:

Specifications:

- Brushed Nickel (-009) (plated)
- · Steel Construction
- · Etched White Linen glass diffuser
- · Design features a domed, linen finish glass diffuser.
- · Diffuser is discreetly supported from metal fittings encloses an energy-efficient light source
- 1600 source lumens 80 lumens/watt (source)
- · 3000K color temperature, 90+ CRI.
- · This fixture is not dimmable.
- Fixture covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included



Performance:

Number of Modules	1	
Input Power	20w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	1600/80 (LM-82)	
Lumens/LPW (Delivered)	1000/50 (LM-79)	
ССТ	3000 K	
CRI	90+	
Life (hours)	(L70/TM-21)	
FCC	FCC Title 47, Part 15, Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cETLus Damp location listed	

Dimensions:

Diameter: 12" Height: 4-1/4"

Glass Width: 11-3/4" Height: 3"