

LED Flush Mount

Project:

Fixture Type:

Contact:

Ceiling mounted • Damp location listed PROGRESS LED



P350101-009-30

Images:

The 13-1/2 inch LED Flush mount offers traditional form factor for ambient illumination. The etched glass dominates the design with its distinctive and sculptural bowl. The elegant glass is paired with a metallic frame in a Brushed Nickel finish.

Specifications:

Description:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Etched Glass globe
- LED Module is replaceable (part # 93074253)
- LED Flush mount offers traditional form factor for ambient illumination
- The etched glass dominates the design with its distinctive and sculptural bowl
- Popular Brushed Nickel finish
- The elegant glass is paired with a metallic frame
- A natural choice for closets, hallways and smaller areas within the home
- Features 25-watt integrated LED to deliver energy savings and reduce long-term maintenance costs
- 1770 lumens, 70 lumens per watt (source)
- 3000K color temperature, 90CRI
- ENERGY STAR certified
- California JA8 certified.
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified
- Meets California Title 24 JA8-2016

Performance:

| Number of Modules | 1 | Glass Widtł Heigł |
|------------------------|-------------------------------------|-------------------------|
| Input Power | 25w | |
| Input Voltage | 120 V | |
| Input Frequency | 60 Hz | |
| Lumens/LPW (Source) | 1770/70 (LM-82) | |
| Lumens/LPW (Delivered) | 1446/56.9 (LM-79) | |
| ССТ | 3000 К | |
| CRI | 90 CRI | |
| Life (hours) | 60,000 (L70/TM-21) | |
| FCC | Meets FCC Title 47, Part 15 Class B | |
| Min. Start Temp | -30 °C | |
| Warranty | 5 year limited warranty | |
| Labels | cCSAus Damp location listed | |
| | ENERGY STAR [®] qualified | |
| | Meets California Title 24 JA8-2016 | |



Dimensions:

Diameter: 13-1/2" Height: 4-1/2"

Glass Width: 10" Height: 3-1/4"



LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



Dimming Notes:

P350101 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

| Lutron Diva DVELV-300P | |
|----------------------------------|--|
| Lutron Nova T NTELV-300 | |
| Lutron Caseta | |
| Lutron Ariadni AY-600P | |
| Lutron Lumea LG-603PG | |
| Leviton SureSlide 6672 | |
| Leviton SureSlide 6674 | |
| Lutron Ariadni AYCL-153P | |
| Lutron Skylark Contour CTCL-153P | |
| Lutron Diva DVCL-153P | |
| Cooper Devine AL DAL06P | |
| Lutron Maestro MACL-153M | |
| Lutron Ariadni AYLV-600P | |
| Lutron Maestro MA-600 | |
| Lutron NOVA T NTLV-600 | |
| lutron Maestro MAELV-600 | |
| Lutron spacer/system SPSELV-600 | |
| Lutron Nova N-600 | |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.