

Project:

Fixture Type: Location:

Contact:

Images:

One-Light Flush Mount

Ceiling flush mounted • Damp location listed PROGRESS LED



P3658-0930K9

One light 11 inch LED flush mount adorned with industrial-inspired accents and etched glass. Brushed Nickel finish.

Specifications:

Description:

- Brushed Nickel (-09) (plated)
- Steel Construction
- Etched glass bowl
- LED Module is replaceable (part # 93053641)
- Industrial style inspired.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	861/51.9 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR [®] qualified



Dimensions:

Diameter: 11" Height: 4-1/8"



One-Light Flush Mount



P3658-0930K9

Dimming Notes:

P3658 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T NTELV-300
Lutron	Vierti VTELV-600
Lutron	Maestro MAELV-600
Lutron	spacer/system SPSELV-600
Leviton	Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.