

One-Light Flush Mount

 Ceiling flush mounted • Damp location listed **PROGRESS LED**


P3673-3130K9

Description:

One-light 12" LED flush mount with etched glass surrounded by a die-cast aluminum frame. Ideal for indoor and outdoor applications. Black finish.

Specifications:

- Black (-31) (powder coat paint)
- Die-cast aluminum Construction
- Frosted glass bowl
- LED Module is replaceable (part # 93053641)
- LED flush mount.
- Etched glass surrounded by a die-cast aluminum frame.
- Ideal for indoor and outdoor applications.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	742/44.4 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements for outdoor use only

Images:



Dimensions:

Diameter: 10-5/8"
Height: 4-7/8"

P3673-3130K9

Dimming Notes:

P3673 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Verti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.