

One-Light LED Semi-flush Mount

Project:

Fixture Type: Location:

Contact:

Ceiling mounted • Damp location listed PROGRESS LED



P3683-0930K9

Harkening back to a simpler time, the Inspire Collection freshens traditional forms with flowing lines. Inspire features an etched glass diffuser with off-white linen shades.

Specifications:

Description:

- Brushed Nickel (-09) (plated)
- Steel Construction
- Off-white linen shade, Etched glass diffuser
- LED Module is replaceable (part # 93074038)
- + Etched glass diffuser provides softened illumination
- 1,452 lumens 83 lumens/watt (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified
- Meets California Title 24 JA8-2016

Performance:

| Number of Modules | 1 | |
|------------------------|-------------------------------------|-----------|
| Input Power | 17w | Di |
| Input Voltage | 120 V | Dia |
| Input Frequency | 60 Hz | He |
| Lumens/LPW (Source) | 1211/71.2 (LM-82) | |
| Lumens/LPW (Delivered) | 938/53.6 (LM-79) | CL |
| CCT | 3000 K | Gla Wi |
| CRI | 90+ CRI | Ler |
| Life (hours) | 60,000 (L70/TM-21) | He |
| FCC | Meets FCC Title 47, Part 15 Class B | |
| Min. Start Temp | -30 ℃ | |
| Max. Operating Temp | 30 °C | |
| Warranty | 5 year warranty | |
| Labels | cCSAus Damp location listed | |
| | ENERGY STAR [®] qualified | |
| | Meets California Title 24 JA8-2016 | |





Dimensions:

Diameter: 13" Height: 10-5/8"

Glass Width: 13" Length: 13" Height: 5-1/2"



One-Light LED Semi-flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



P3683-0930K9

Dimming Notes:

P3683 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

| utron Diva DVELV-300P | |
|--------------------------------------|--|
| utron Nova T NTELV-300 | |
| utron Caseta | |
| utron Ariadni AY-600P | |
| eviton Illumatech IPI06-1LZ | |
| utron Lumea LG-603PG | |
| eviton SureSlide 6672 | |
| eviton SureSlide 6674 | |
| utron Ariadni AYCL-153P | |
| utron Skylark Contour CTCL-153P | |
| Lutron Diva DVCL-153P | |
| Pass & Seymour Harmony DCL453PTCCCV6 | |
| utron Toggler TGCL-153P | |
| utron Maestro MACL-153M | |
| utron Ariadni AYLV-600P | |
| utron Maestro MA-600 | |
| utron NOVA T NTLV-600 | |
| utron Maestro MAELV-600 | |
| utron spacer/system SPSELV-600 | |
| utron Renoir II AWRMG-EAW | |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.