

## Pivot LED

 Ceiling Stem Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Pivot LED Collection Six-Light Matte Black Modern Style Chandelier with Downlight

### Specifications:

- Frosted Acrylic Square/Rectangular
- Frosted Polycarbonate Round Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.125 in W., 1.375 in ht., 5.125 in depth
- Mounting backplate for outlet box included
- 120 in of wire supplied

### Performance:

Number of Lights	6 + Downlight
Input Power	25 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,062/45 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed Meets California Title 24 JA8-2019

# P400260-031-30



### Dimensions:

Diameter: 28-1/4 in  
 Height: 8-3/4 in  
 Overall Ht. W/Stem: 62-1/2 in

# P400260-031-30

**Dimming Notes:**

---

P400260-031-30 is designed to be compatible with many ELV controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

Lutron\_DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.