

## One-Light Pendant

 Hanging mounted • Damp location listed **PROGRESS LED**


### Description:

These timeless and classic LED pendants feature designer oriented details and cylindrical polished opal glass. Can be displayed singularly or in groupings of two or more in a variety of spaces, such as Modern Farmhouse, Coastal and Mid-Century Modern environments. Brushed Nickel finish.

### Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Glossy Opal Glass cylinder
- Cylindrical shaped LED pendant
- These timeless and classic LED pendants feature designer oriented details and polished opal glass
- One light 9W medium LED lamp
- Warm white, 3000K, color temperature, 90 CRI
- 624 lumens, 66 lumens per watt (source)
- Can be displayed singularly or in groupings of two or more in a variety of spaces, such as Modern Farmhouse, Coastal and Mid-Century Modern environments
- Replaceable light engine is California JA8 certified
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

### Performance:

|                        |   |
|------------------------|---|
| Number of Modules      | 1   |
| Input Power            | 9w  |
| Input Voltage          | 120 V   |
| Input Frequency        | 60 Hz   |
| Lumens/LPW (Source)    | 624/66 (LM-82)  |
| Lumens/LPW (Delivered) | 581/61.2 (LM-79)  |
| CCT                    | 3000 K  |
| CRI                    | 90 CRI  |
| Life (hours)           | 60,000 (L70/TM-21)  |
| FCC                    | Meets FCC Title 47, Part 15 Class B   |
| Min. Start Temp        | -30 °C  |
| Max. Operating Temp    | 30°C  |
| Warranty               | 5 year limited warranty   |
| Labels                 | cCSAus Damp location listed<br>ENERGY STAR® qualified<br>Meets California Title 24 JA8-2016 |

## P500065-009-30

### Images:



### Dimensions:

Diameter: 4-3/8"  
Height: 13-1/2"  
Overall Ht. W/Cord: 124-1/2"

Glass  
Width: 4-3/8"  
Height: 10-1/2"

## P500065-009-30

### Dimming Notes:

---

P500065 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Leviton SureSlide 6672

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYL-600P

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.