

| Fixture Type | ٥. |  |  |  |  |
|--------------|----|--|--|--|--|
|--------------|----|--|--|--|--|

Contact:

### Globe LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED



#### **Description:**

A distinctive classic globe pendant is accented by a striking metal black cap. The cap holds a beautiful opal glass shade ready to emit gentle illumination. This versatile pendant can be displayed as a single fixture or in groups of two or more to create a custom lighting design for your home.

#### **Specifications:**

- · Opal glass Globe
- $\boldsymbol{\cdot}$  The cap holds a beautiful opal glass shade ready to emit gentle illumination.
- · A distinctive classic globe pendant is accented by a striking metal black cap.
- This versatile pendant can be displayed as a single fixture or in groups of two or more to create a custom lighting design for your home.
- · Ideal for any foyer, kitchen, or dining room.
- Perfect for mid-century modern, transitional, modern, or contemporary settings.
- · Measures 8-inch width by 9-3/4-inch height.
- · Overall length with cord is 122"
- · Uses one LED module (9w max).
- · Compatible with many Triac/ELV dimmers (see dimming controls)
- · Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.5 in W., 1 in ht., 5.5 in depth
- 1/8 IP mounting plate for outlet box included
- · 120 in of wire supplied

#### **Performance:**

| 66 (LM-82)                     |
|--------------------------------|
| K                              |
| !!                             |
| ) (L70/TM-21)                  |
| itle 47, Part 15, Class B      |
| Limited Warranty               |
| us Damp Location Listed        |
| GY STAR® qualified             |
| S California Title 24 JA8-2016 |
|                                |

## P500147-031-30




#### **Dimensions:**

Diameter: 8 in Height: 9-3/4 in

Overall Ht. W/Cord: 122 in

Opal glass Globe Width: 7-7/8 in Height: 7-3/8 in





### Globe LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED



## Dimming Notes:

P500147-031-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

# P500147-031-30

#### **Dimming Controls:**

Lutron\_Diva DVELV-300P

Lutron\_Nova T NTELV-300

Lutron\_Caseta

Lutron\_Ariadni AY-600P

Leviton\_Illumatech IPI06-1LZ

Leviton\_SureSlide 6672

Lutron\_Ariadni AYCL-153P

Lutron\_Skylark Contour CTCL-153P

Lutron\_Diva DVCL-153P

Lutron\_Toggler TGCL-153P

Lutron\_Maestro MACL-153M

Lutron\_Ariadni AYLV-600P

Lutron\_Nova T NTLV-600

Lutron\_Maestro MAELV-600

Lutron\_spacer/system SPSELV-600

Leviton\_Renoir II AWRMG-EAW

Lutron\_Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.