

Project:
Fixture Type:
Location:

# Planck LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED

Contact:

## **Description:**

Provide a dramatic architectural lighting design to any space with this LED pendant. A smooth metal beam with a black finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings. The frame holds a polycarbonate shade in place to complete the design.

### **Specifications:**

- · White polycarbonate Diffuser
- $\boldsymbol{\cdot}$  The frame holds a polycarbonate shade in place to complete the design.
- A smooth metal beam with a black finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings.
- · Provide a dramatic architectural lighting design to any space.
- · Ideal for any hallway, foyer, kitchen, or dining room.
- · Perfect for transitional, modern, or contemporary settings.
- Measures 47-1/4-inch width by 1-3/8-inch height.
- · Uses one integrated LED that is included (39w max).
- · Compatible with many Triac/ELV dimmers (see dimming controls)
- $\boldsymbol{\cdot}$  Includes installation instructions and mounting hardware.
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 21.5 in W., 4.75 in ht., 1.25 in depth
- · Mounting backplate for outlet box included
- 108 in of wire supplied

#### **Performance:**

Number of Modules	1
Input Power	39 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2,900/74 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016

# P500276-031-30



### **Dimensions:**

Width: 47-1/4 in Height: 1-3/8 in Depth: 1-3/4 in

Overall Ht. W/Wire: 113 in

White polycarbonate Diffuser

Width: 46-7/16 in Height: 0-1/16 in



# Planck LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED

P500276-031-30

## **Dimming Notes:**

P500276-031-30 is designed to be compatible with many Triac/Forward Phase controls

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls:**

Leviton 6672

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.