

## Geodesic LED

Cable Suspension Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Geodesic LED Collection Matte Black LED Mid-Century Modern Large Pendant Hanging Light

### Specifications:

- Frosted Acrylic Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5 in W., 1.6 in ht., 5 in depth
- Swivel mounting strap for outlet box included
- 96 in of wire supplied 90 in

### Performance:

Number of Modules	1
Input Power	38 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	3,373/88 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed Meets California Title 24 JA8-2019

## P500320-031-30



### Dimensions:

Length: 27-1/8 in  
Diameter: 27-1/8 in  
Height: 12-1/4 in  
Overall Ht. W/Cables: 103-3/4 in

Frosted Acrylic Diffuser  
Width: 11-15/16 in  
Height: 0.039 in

# P500320-031-30

## Dimming Notes:

---

P500320-031-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Leviton\_6674

Lutron\_NTEVL-300

Lutron\_DVELV-300P

Lutron\_Caseta Wireless

Lutron\_AYCL-153P

Lutron\_SCL-153P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.