

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Pendant

Ceiling stem hung with 6 links of chain • Damp location listed PROGRESS LED





Description:

Inspired by vintage light fixtures found in early 20th century train stations. The LED one-light pendant has a metal shade and is stem hung. 3000K, 90+ CRI, 1,211 lumens 71.2 lumens/watt per module (source). Brushed Nickel finish.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel Construction
- Spun metal shade
- LED Module is replaceable (part # 93053641)
- Inspired by vintage light fixtures found in early 20th century train stations.
- One-light pendant has a spun metal shade.
- Stem-hung with 90 degree swivel.
- Includes one 6", four 12" stems and 6 links of chain.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 15 feet of wire supplied
- · One 6", four 12" lengths of stem included
- · Six links of 9 gauge chain supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements

Performance:

Number of Modules	1	
Input Power	17w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	1211/71.2 (LM-82)	
CCT	3000 K	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cCSAus Damp location listed	
	ENERGY STAR® qualified	
	Meets California Title 24 high efficacy requirements	

P5024-0930K9

Images:



Dimensions:

Diameter: 12" Height: 9-1/4"

Overall Ht. W/Stem: 75-1/4"



One-Light Pendant





P5024-0930K9

Dimming Notes:

P5024 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T NTELV-300
Lutron	Vierti VTELV-600
Lutron	Maestro MAELV-600
Lutron	spacer/system SPSELV-600
Leviton	Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.