

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED



Description:

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 29w LED pendant is 3000K in a Satin Aluminum finish with a painted silver interior. This is an ideal fixture for residential and commercial applications.

Specifications:

- Satin Aluminum (-16) (powder coat paint)
- Aluminum Construction
- Satin Aluminum, painted silver inside aluminum shade, White acrylic Diffuser
- · LED Module is replaceable (part # 1911098)
- · Inspired to enhance modern home decor.
- · Complements a wide array of styles from industrial to farmhouse.
- Satin Aluminum finish with a painted silver interior.
- · Dimmable to 10% with many ELV dimmers
- · 2197 lumens 75.8 lumens/watt (source)
- · 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	29w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	2197/75.8 (LM-82)
Lumens/LPW (Delivered)	1086/37.2 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Dry location listed
	ENERGY STAR® qualified

P5342-1630K9

Images:



Dimensions:

Diameter: 22" Height: 11-3/4"

Overall Ht. W/Cord: 131-1/2"

Glass Width: 22" Length: 22" Glass 2 Width: 5-13/16" Length: 5-13/16" Height: 0-1/2"



One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED



P5342-1630K9

Dimming Notes:

P5342 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.