

roject:
ixture Type:
ocation:
ontact:

# One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED



# **Description:**

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 29w LED pendant is 3000K in an Antique Bronze finish with a painted gold interior. This is an ideal fixture for residential and commercial applications.

### **Specifications:**

- · Antique Bronze (-20) (painted)
- Aluminum Construction
- Antique Bronze, painted gold inside aluminum shade, White acrylic Diffuser
- · LED Module is replaceable (part # 1911098)
- · Inspired to enhance modern home decor.
- · Complements a wide array of styles from industrial to farmhouse.
- · Antique Bronze finish with a painted gold interior.
- · Dimmable to 10% with many ELV dimmers
- · 2197 lumens 75.8 lumens/watt (source)
- · 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified

#### Performance:

Number of Modules	1
Input Power	29w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	2197/75.8 (LM-82)
Lumens/LPW (Delivered)	1086/37.2 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Dry location listed
	ENERGY STAR® qualified

# P5342-2030K9

#### Images:



#### **Dimensions:**

Diameter: 22" Height: 11-3/4"

Glass

Overall Ht. W/Cord: 131-1/2"

Width: 22" Length: 22" Glass 2 Width: 5-13/16" Length: 5-13/16" Height: 0-1/2"



# One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED





P5342-2030K9

# **Dimming Notes:**

P5342 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.