

#### Project:

Fixture Type:

Location:

Contact:

## One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED



P5342-3030K9

#### **Description:**

Images:

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 29w LED pendant is 3000K in a White finish with a painted silver interior. This is an ideal fixture for residential and commercial applications.

#### **Specifications:**

- White (-30) (painted) •
- Aluminum Construction •
- White, painted silver inside aluminum shade, White acrylic Diffuser .
- LED Module is replaceable (part # 1911098)
- · Inspired to enhance modern home decor.
- Complements a wide array of styles from industrial to farmhouse. .
- · White finish with a painted silver interior.
- · Dimmable to 10% with many ELV dimmers
- · 2197 lumens 75.8 lumens/watt (source)
- 3000K color temperature, 90+ CRI. •
- Dimmable to 10% brightness (See Dimming Notes) •
- Canopy covers a standard 4" octagonal recessed outlet box • . Mounting strap for outlet box included
- . 6" of wire supplied
- .

### ENERGY STAR<sup>®</sup> gualified

#### **Performance:**

| Number of Modules      | 1                                   | Dia<br>Hei<br>Ove                             |
|------------------------|-------------------------------------|---|
| Input Power            | 29w                                 |   |
| Input Voltage          | 120 V                               |   |
| Input Frequency        | 60 Hz                               |   |
| Lumens/LPW (Source)    | 2197/75.8 (LM-82)                   | Gla<br>Wic<br>Len<br>Gla<br>Wic<br>Len<br>Hei |
| Lumens/LPW (Delivered) | 1086/37.2 (LM-79)                   |   |
| ССТ                    | 3000 K                              |   |
| CRI                    | 90+                                 |   |
| Life (hours)           | 60,000 (L70/TM-21)                  |   |
| FCC                    | Meets FCC Title 47, Part 15 Class B |   |
| Min. Start Temp        | -30 °C                              |   |
| Max. Operating Temp    | 30 ℃                                |   |
| Warranty               | 5 year warranty                     |   |
| Labels                 | cCSAus Dry location listed          |   |
|                        | ENERGY STAR <sup>®</sup> qualified  |   |
|                        |                                     |   |

#### **Dimensions:**

ameter: 22" eight: 11-3/4" verall Ht. W/Cord: 131-1/2"

ass idth: 22" ngth: 22" ass 2 idth: 5-13/16" ngth: 5-13/16" eight: 0-1/2"



# One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED



### P5342-3030K9

#### **Dimming Notes:**

P5342 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

#### **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.