

3IN Cylinders

Ceiling Mounted • Damp Location Listed PROGRESS LED



Description:

3" Antique Bronze Surface Mount Modern Adjustable LED Cylinder

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.1 in W., 1.3 in ht., 5.1 in depth
- Mounting Plate
- 6 in of wire supplied

Performance:

| | |
|------------------------|---|
| Input Power | 12 W |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 986/82 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 50000 (L70/TM-21) |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Warranty | 5-year Limited Warranty |
| Labels | cCSAus Damp Location Listed ENERGY STAR® qualified Meets California Title 24 JA8-2016 |

P550139-020-30



Dimensions:

Diameter: 5 in
 Height: 7-3/8 in



Photometrics:

P550139-020-30

| ELECTRICAL DATA | P550139-020-30 |
|------------------------|--------------------------------|
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| THD | <20% |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Operating Temperature | -40 °C to 40 °C |
| Dimming | Yes* |

*See Dimming Notes for more information

Dimming Notes:

P550139-020-30 is designed to be compatible with many ELV/Reverse Phase Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P

Lutron_Diva DVELV-300P

Lutron_Caseta Wireless

Leviton_SureSlide 6672

Lutron_Ariadni AYCL-153P

Lutron_Toggler TGCL-153PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P550139-020-30