

Project:		
Fixture Type:		
Location:		
Contact:		

# Wall Lantern

Wall mounted • Wet location listed PROGRESS LED





## **Description:**

Inspired by traditional lantern styles, Whitacre incorporates handsome details. Clear seeded glass surrounds an etched opal glass candle diffuser. An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.

## **Specifications:**

- · Antique Bronze (-020) (painted)
- Aluminum construction
- Clear Seeded with Etched Ivory diffuser Glass globe
- · Inspired by traditional lantern styles, Whitacre incorporates handsome details
- · An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.
- Clear seeded glass surrounds an etched opal glass candle diffuser
- Includes one 9-watt replaceable LED modulesWarm white, 3000K, color temperature, 90 CRI
- 624 lumens, 66 lumens per watt (source)
- Wall lantern adds illumination to walkways and pathways to enhance safety and security
- Replaceable light engine is California JA8 certified
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016

#### **Performance:**

Number of Modules	1		
Input Power	9w		
Input Voltage	120 V		
Input Frequency	60 Hz		
Lumens/LPW (Source)	624/66 (LM-82)		
Lumens/LPW (Delivered)	348/36.6315789473684 (LM-79)		
ССТ	3000 K		
CRI	90 CRI		
Life (hours)	60,000 (L70/TM-21)		
FCC	Meets FCC Title 47, Part 15 Class B		
Min. Start Temp	-30 °C		
Max. Operating Temp	30°C		
Warranty	5 year limited warranty		
Labels	cCSAus Wet location listed		
	ENERGY STAR® qualified		
	Meets California Title 24 JA8-2016		

## P560068-020-30

#### Images:



#### **Dimensions:**


Width: 7-7/8" Depth: 8" Height: 14-3/8" H/CTR: 3-5/8"

Width: 5" Height: 8" Glass 2 Width: 3" Length: 3" Height: 3"

Glass



# Wall Lantern



P560068-020-30

## **Dimming Notes:**

P560068 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Leviton SureSlide 6672

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.