

#### Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED

# energy sta

#### **Description:**

Wall Lantern

Images:

Inspired by traditional lantern styles, Whitacre incorporates handsome details. Clear seeded glass surrounds an etched opal glass candle diffuser. An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.

#### **Specifications:**

- · Antique Bronze (-020) (painted)
- Aluminum construction
- Clear Seeded with Etched Ivory diffuser Glass globe
- Inspired by traditional lantern styles, Whitacre incorporates handsome details
- An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.
- · Clear seeded glass surrounds an etched opal glass candle diffuser
- Includes one 9-watt replaceable LED modulesWarm white, 3000K, color temperature, 90 CRI
- · 624 lumens, 66 lumens per watt (source)
- · Wall lantern adds illumination to walkways and pathways to enhance safety and security
- Replaceable light engine is California JA8 certified
- · Can also be used in interior settings and paired with decorative fixtures for creative design ideas.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 JA8-2016

#### Performance:

		Depti
Number of Modules	1	Heigł H/CT
Input Power	9w	ii/ci
Input Voltage	120 V	
Input Frequency	60 Hz	Glass
Lumens/LPW (Source)	624/66 (LM-82)	Width Heigh
Lumens/LPW (Delivered)	351/37.7 (LM-79)	Glass
CCT	3000 K	Width
CRI	90 CRI	Lengt Heigh
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30°C	
Warranty	5 year limited warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR <sup>®</sup> qualified	
	Meets California Title 24 JA8-2016	



P560069-020-30

#### **Dimensions:**

Width: 10" Depth: 10" Height: 18" H/CTR: 4"

Glass Width: 6-1/2" Height: 10-1/2" Glass 2 Width: 3-5/8" Length: 3-5/8" Height: 3-5/8"



## Wall Lantern

Wall mounted • Wet location listed PROGRESS LED

### P560069-020-30

nergy

#### **Dimming Notes:**

P560069 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

#### **Dimming Controls**

Lutron Diva DVELV-300P
Lutron Nova T NTELV-300
Lutron Caseta
Lutron Ariadni AY-600P
Leviton Illumatech IPI06-1LZ
Leviton SureSlide 6672
Lutron Ariadni AYCL-153P
Lutron Skylark Contour CTCL-153P
Lutron Diva DVCL-153P
Lutron Toggler TGCL-153P
Lutron Maestro MACL-153M
Lutron Ariadni AYLV-600P
Lutron NOVA T NTLV-600
lutron Maestro MAELV-600
Lutron spacer/system SPSELV-600
Lutron Renoir II AWRMG-EAW
Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.