

LED Wall Lantern

Wall mounted • Wet location listed 

P560136-031-30

Description:

This energy efficient LED wall lantern features a Black finish on a die-cast aluminum frame. This fixture includes integrated LED technology with no bulbs to replace. The frosted glass panels have a warm quality that adds to the lantern's traditional design.

Specifications:

- Black (-031) (painted)
- Die-Cast Aluminum Construction
- Etched glass Panels
- This energy efficient LED wall lantern features a die-cast aluminum frame
- This fixture includes integrated LED technology
- Features frosted glass panels
- The one-light wall lantern is suited for placement at a front or back door, along exterior walls or within an covered outdoor living area
- Measures 5-5/8in dia. x 8-7/8in ht.
- 11w integrated LED, 564 delivered lumens 47 lumens/watt (delivered) 3000K color temperature, 80+ CRI.
- CSA Safety listed for use in wet locations
- Progress Lighting products are designed for exceptional quality, reliability, and functionality
- Includes installation instructions and mounting hardware
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting swivel mounting strap for outlet box included
- 6" of wire supplied
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| | |
|------------------------|---|
| Number of Modules | 1 |
| Input Power | 11w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 564/47 (LM-79) |
| CCT | 3000 K |
| CRI | 82 CRI |
| Life (hours) | 36,000 (L70/TM-21) |
| FCC | FCC Title 47, Part 15, Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | -30°C |
| Warranty | 5 year limited warranty |
| Labels | cCSAus Wet location listed |
| | Meets California Title 24 high efficacy requirements for outdoor use only |

Images:



Dimensions:

Square: 5-5/8"
Depth: 6-5/8"
Height: 8-7/8"
H/CTR: 6-5/8"

Etched glass panels
Width: 4-3/16"
Height: 4-1/2"