

Project:			
Fixture Type:			
Location:			
Contact:			

6IN CYL RNDS

Wall Mounted • Wet Location Listed PROGRESS LED

Description:

6" LED Outdoor Up/Down Modern Antique Bronze Wall Cylinder with Glass Top Lens

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 4.45 in W., 4.45 in ht., 0.65 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied

Performance:

Number of Lights	2		
Input Power	64 W		
Input Voltage	120 VAC		
Input Frequency	60 Hz		
Lumens/LPW (Delivered)	1,837/29 (LM-79)		
CCT	3000 K		
CRI	90 CRI		
Life (hours)	50000 (L70/TM-21)		
EMI/RFI	FCC Title 47, Part 15, Class B		
Warranty	5-year Limited Warranty		
Labels	cCSAus Wet Location Listed		
	Meets California Title 24 JA8-2019		

P560293-020-30



Dimensions:

Length: 6 in Extends: 8-15/16 in Height: 18 in



6IN CYL RNDS

Wall Mounted • Wet Location Listed PROGRESS LED

Dimming Notes:

P560293-020-30

 $\ensuremath{\mathsf{P560293\text{-}020\text{-}30}}$ is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron NTEVL-300

Lutron DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.