

Fixture Type:
Location:

Contact:

District LED

Wall Mounted • Wet Location Listed PROGRESS LED



Description:

District Collection LED Large Wall Lantern

Specifications:

- Antique Bronze, Painted White Inside Aluminum Shade
- · White Acrylic Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" recessed outlet box: 5.125 in W., 1.625 in ht., 5.125 in depth
- · Mounting strap for outlet box included
- \cdot 6 in of wire supplied
- · Dark Sky compliant

Performance:

Number of Modules	1
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	479/61.1 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Wet Location Listed
	ENERGY STAR® qualified

P5623-2030K9



Dimensions:

Width: 12 in Depth: 13-1/4 in Height: 10-1/2 in H/CTR: 5 in

Antique Bronze, Painted White Inside Aluminum Shade

Width: 12 in Height: 7-15/16 in

White Acrylic Diffuser Width: 2-7/8 in Height: 0-13/16 in



District LED

Wall Mounted • Wet Location Listed PROGRESS LED



Dimming Notes:

 ${\tt P5623-2030K9} \ is \ designed \ to \ be \ compatible \ with \ many \ {\tt ELV/Reverse} \ Phase \ controls.$

The following is a partial list of known compatible dimmer controls.

P5623-2030K9

Dimming Controls:

Lutron_Nova T NTELV-300

Lutron_Vierti VTELV-600

Lutron_Maestro MAELV-600

Lutron_spacer/system SPSELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.