

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Wall Sconce W/HAL AC LED Module

Wall mounted • Wet location listed PROGRESS LED



Description:

Modern geometric outdoor LED sconces are designed to complement a range of residential and commercial architectural styles. ADA compliant. 9w LED is 3000K, 90+ CRI in a Black cast aluminum shade. Dark Sky compliant.

Specifications:

- · Black (-31) (powder coat paint)
- · Cast aluminum Construction
- · Black cast aluminum shade, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- · Modern geometric outdoor LED sconces.
- Designed to complement a range of residential and commercial architectural styles.
- · Dark Sky compliant.
- · 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- · Dimmable to 10% brightness (See Dimming Notes)
- · Unit covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- · 6" of wire supplied
- · Complies with "Americans with Disabilities Act" ADA
- · ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only



Images:



Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	388/49.7 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements
	for outdoor use only

Dimensions:

Width: 5-1/4" Depth: 4" Height: 4-3/4" H/CTR: 2-3/8"

Glass

Width: 4-1/16" Length: 5-3/16" Height: 4-11/16" Glass 2 Width: 2-7/8" Length: 2-7/8" Height: 0-11/16"



One-Light Wall Sconce W/HAL AC LED Module

Wall mounted • Wet location listed PROGRESS LED



P5634-3130K9

Dimming Notes:

P5634 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.