

| Droi | oct. |
|------|------|
| PIO | ICUL |
| | |

Fixture Type: Location:

Contact:

One-Light Wall Sconce W/HAL AC LED Module

Description:

Modern geometric outdoor LED sconces are designed to complement a range of residential and commercial architectural styles. ADA compliant. 9w LED is 3000K, 90+ CRI in a Black cast aluminum square shade. Dark Sky compliant.

Specifications:

- Black (-31) (powder coat paint)
- Cast aluminum Construction
- Black cast aluminum shade, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- Modern geometric outdoor LED sconces.
- Designed to complement a range of residential and commercial architectural styles.
- Dark Sky compliant.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" ADA
- ENERGY STAR[®] qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| | | NV/* 1.1 |
|------------------------|--|--|
| Number of Modules | 1 | Width: Depth: Height H/CTR |
| Input Power | 9w | |
| Input Voltage | 120 V | |
| Input Frequency | 60 Hz | |
| Lumens/LPW (Source) | 623/69.2 (LM-82) | Glass Width: Length Height Glass : Width: Length Height |
| Lumens/LPW (Delivered) | 352/49.6 (LM-79) | |
| CCT | 3000 K | |
| CRI | 90+ | |
| Life (hours) | 60,000 (L70/TM-21) | |
| FCC | Meets FCC Title 47, Part 15 Class B | |
| Min. Start Temp | -30 ℃ | |
| Max. Operating Temp | 30 °C | |
| Warranty | 5 year warranty | |
| Labels | cCSAus Wet location listed | |
| | ENERGY STAR [®] qualified | |
| | Meets California Title 24 high efficacy requirements | |
| | for outdoor use only | |

.

Wall mounted • Wet location listed PROGRESS LED



P5635-3130K9

Images:



Dimensions:

Width: 6-1/8" Depth: 4" Height: 5" H/CTR: 2-3/8"

Glass Width: 4-1/16" Length: 6-1/16" Height: 4.-15/16" Glass 2 Width: 2-7/8" Length: 2-7/8" Height: 0-11/16"



One-Light Wall Sconce W/HAL AC LED Module



P5635-3130K9

Dimming Notes:

P5635 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.