

One-Light Outdoor

Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED



P5750-2030K9

Images:

Craftsman styling marries traditional and rustic details. Artistic glass with die-cast aluminum powder coated finish. This one-light LED medium wall lantern is 3000K, 90+ CRI and 623 lumens (source).

Specifications:

Description:

- · Antique Bronze (-20) (powder coat paint)
- · Aluminum Construction
- Etched Seedy Umber Watermark glass shade •
- LED Module is replaceable (part # 93054049)Antique Bronze finish. .
- Marriage of traditional and rustic styling. .
- · Artistic glass.
- · Meets California Title 24 high efficacy requirements for outdoor use only.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- · Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included •
- 6" of wire supplied .
- ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

		Dim
Number of Modules	1	Dim
Input Power	9w	Widt
Input Voltage	120 V	Dep Heig H/C
Input Frequency	60 Hz	
Lumens/LPW (Source)	623/69.2 (LM-82)	
Lumens/LPW (Delivered)	245/30.625 (LM-79)	
ССТ	3000 K	Gla: Wid Len Hei
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR [®] qualified	
	Meets California Title 24 high efficacy requirements	
	for outdoor use only	



ensions:

th: 8-1/2" th: 9-3/8" ght: 11-1/4" TR: 4-1/4"

s th: 6-3/8" gth: 6-3/8" , ght: 8"



One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED



P5750-2030K9

Dimming Notes:

P5750 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.