

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED





Description:

Craftsman styling marries traditional and rustic details. Artistic glass with die-cast aluminum powder coated finish. This one-light LED large wall lantern is 3000K, 90+ CRI and 623 lumens (source).

Specifications:

- · Antique Bronze (-20) (powder coat paint)
- · Aluminum Construction
- Etched Seedy Umber Watermark glass shade
- LED Module is replaceable (part # 93054049)Antique Bronze finish.
- Marriage of traditional and rustic styling.
- · Artistic glass.
- · Meets California Title 24 high efficacy requirements for outdoor use only.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	916/31.5 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements
	for outdoor use only

P5751-2030K9

Images:



Dimensions:

Width: 10-5/8" Depth: 11-5/8" Height: 15-1/2" H/CTR: 3-3/8"

Glass Width: 8-1/8" Length: 8-1/8" Height: 10-1/8"



One-Light Outdoor





Dimming Notes:

P5751 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.