

Project:

Fixture Type:

Location:

Contact:

One-Light Linear Lantern

Wall vertical only mounted • Wet location listed PROGRESS LED



Description:

Images:

Clean lines are up front and center for these modern LED outdoor sconces. Valera features a die-cast aluminum frame and matte white, acrylic diffuser. Energy efficient LED source offers 3000K color temperature and 90+CRI output. Title 24 compliant. One-light 9w LED wall lantern in a Brushed Nickel finish.

Specifications:

- Brushed Nickel (-09) (plated)
- Aluminum Construction
- Matte White acrylic diffuser
- LED Module is replaceable (part # 93054049)
- Modern LED outdoor sconce.
- Clean lines are central to design.
- Features a die-cast aluminum frame and matte white, acrylic diffuser.
- 623 lumens 69.2 lumens/watt (source)
- 3000K color temperature, 90+ CRI.
- Wall mount vertical only.
- Dimmable to 10% brightness (See Dimming Notes)
- Chassis covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" ADA
- ENERGY STAR[®] qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

		Dope
Number of Modules	1	Heig H/C1
Input Power	9w	
Input Voltage	120 V	
Input Frequency	60 Hz	Glass
Lumens/LPW (Source)	623/69.2 (LM-82)	Widt Leng
Lumens/LPW (Delivered)	300/38.5 (LM-79)	Heig
ССТ	3000 K	
CRI	90+	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR [®] qualified	
	Meets California Title 24 high efficacy requirements	
	for outdoor use only	



P5800-0930K9

Dimensions:

Width: 5-5/8' Depth: 4" Height: 8" H/CTR: 4"

Glass Width: 3-3/4" Length: 5-3/8" Height: 7-15/16"



One-Light Linear Lantern



P5800-0930K9

Dimming Notes:

P5800 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.