

Project:

Fixture Type: Location:

Contact:

One-Light Wall Lantern

Wall vertical only mounted • Wet location listed PROGRESS LED



Description:

Images:

Clean lines are up front and center for these modern LED outdoor sconces. Valera features a die-cast aluminum frame and matte white, acrylic diffuser. Energy efficient LED source offers 3000K color temperature and 90+CRI output. Title 24 compliant. One-light 17w LED wall lantern in a Brushed Nickel finish.

Specifications:

- Brushed Nickel (-09) (plated)
- Aluminum Construction
- Matte White acrylic diffuser
- LED Module is replaceable (part # 93053641)
- Modern LED outdoor sconce.
- Clean lines are central to design.
- Features a die-cast aluminum frame and matte white, acrylic diffuser.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Wall mount vertical only.
- Dimmable to 10% brightness (See Dimming Notes)
- Chassis covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" ADA
- ENERGY STAR[®] qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1	Heig H/C1
Input Power	17w	n/ci
Input Voltage	120 V	
Input Frequency	60 Hz	Glass
Lumens/LPW (Source)	1211/71.2 (LM-82)	Widtl Leng
Lumens/LPW (Delivered)	580/33.9 (LM-79)	Heig
ССТ	3000 K	
CRI	90+	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 °C	
Warranty	5 year warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR [®] qualified	
	Meets California Title 24 high efficacy requirements	
	for outdoor use only	



P5801-0930K9

Dimensions:

Width: 8-5/8" Depth: 4" Height: 11" H/CTR: 5-1/2"

Glass Width: 3-3/4" Length: 8-3/8" Height: 10-15/16"



One-Light Wall Lantern



P5801-0930K9

Dimming Notes:

P5801 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.