

## **One-Light Outdoor**

#### Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED

# ENERGY STA

### **Description:**

Arrive LED lanterns feature a die-cast aluminum, powder coated frame and heavily textured glass. One-light medium wall lantern. 90+ CRI, 3000K, 623 lumens (source) Energy Star.

### **Specifications:**

- Black (-31) (painted)
- Die-cast aluminum Construction
- Clear Seeded glass panels
- LED Module is replaceable (part # 93054049)
- Die-cast aluminum, powder coated frame.
- Heavily textured glass.
- 90+ CRI, 3000K, 623 lumens. Energy Star.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

### Performance:

| Number of Modules      | 1  | Dim                             |
|------------------------|--|---------------------------------|
| Input Power            | 9w   | Widtł<br>Deptl<br>Heigl<br>H/CT |
| Input Voltage          | 120 V  |                                 |
| Input Frequency        | 60 Hz  |                                 |
| Lumens/LPW (Source)    | 623/69.2 (LM-82)                                     |                                 |
| Lumens/LPW (Delivered) | 392/48.4 (LM-79)                                     |                                 |
| CCT                    | 3000 K   | Glass<br>Widtl<br>Leng<br>Heigl |
| CRI                    | 90 CRI   |                                 |
| Life (hours)           | 60,000 (L70/TM-21)                                   |                                 |
| FCC                    | Meets FCC Title 47, Part 15 Class B                  |                                 |
| Min. Start Temp        | -30 °C   |                                 |
| Max. Operating Temp    | 30 °C  |                                 |
| Warranty               | 5 year warranty                                      |                                 |
| Labels                 | cCSAus Wet location listed                           |                                 |
|                        | ENERGY STAR <sup>®</sup> qualified                   |                                 |
|                        | Meets California Title 24 high efficacy requirements |                                 |
|                        | for outdoor use only                                 |                                 |

### P6068-3130K9

Images:



#### Dimensions:

Width: 7-1/2" Depth: 8-3/4" Height: 11-1/8" H/CTR: 5-1/4"

Glass Width: 0-1/8" Length: 5-1/16" Height: 7-13/16"



# **One-Light Outdoor**

Wall mounted • Wet location listed PROGRESS LED



### P6068-3130K9

### **Dimming Notes:**

P6068 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.