

## Medium Wall Lantern

Wall mounted • Wet location listed



### Description:

The East Haven LED Collection offers modern styling to complement a wide variety of home styles. The one-light medium LED outdoor wall lantern has an Antique Bronze frame that cradles a seeded glass shade. 120V AC replaceable LED module, 623 lumens (source), 3000K color temperature and 90+ CRI.

### Specifications:

- Antique Bronze (-20) (powder coat paint)
- Aluminum Construction
- Clear Seeded glass shade, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- Contemporary styling.
- Features clear seeded glass.
- Powder coated finish.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

### Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	326/41.3 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements for outdoor use only

## P6078-2030K9

### Images:



### Dimensions:

Width: 7-1/2"  
Depth: 9-1/8"  
Height: 9-3/4"  
H/CTR: 4-3/4"

Glass  
Width: 6-1/8"  
Length: 6-1/8"  
Height: 6-1/2"  
Glass 2  
Width: 2-7/8"  
Length: 2-7/8"  
Height: 0-13/16"

**P6078-2030K9****Dimming Notes:**

---

P6078 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.