

# Small Wall Lantern

Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED



# P6084-2030K9

Images:

LED wall lantern with etched umber linen glass. Includes dark sky shield for full cut-off illumination or remove for a traditional lighting effect. 120V AC replaceable LED module, 623 lumens (source), 3000K color temperature and 90+ CRI.

## **Specifications:**

**Description:** 

- Antique Bronze (-20) (powder coat paint)
- Aluminum Construction
- Etched Umber Linen glass cylindrical diffuser
- LED Module is replaceable (part # 93054049)
- Etched umber linen glass.
- · Includes removable dark sky shield for full cut-off illumination.
- Powder coated finish.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

## Performance:

Number of Modules1Input Power9wInput Voltage120 VInput Frequency60 HzLumens/LPW (Source)623/69.2 (LM-82)Lumens/LPW (Delivered)130/17.1 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements for outdoor use only			Dime
Input Voltage120 VInput Frequency60 HzLumens/LPW (Source)623/69.2 (LM-82)Lumens/LPW (Delivered)130/17.1 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelsCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Number of Modules	1	Width: Depth: Height: H/CTR:
Input Frequency60 HzLumens/LPW (Source)623/69.2 (LM-82)Lumens/LPW (Delivered)130/17.1 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Input Power	9w	
Lumens/LPW (Source)623/69.2 (LM-82)Lumens/LPW (Delivered)130/17.1 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Input Voltage	120 V	
Lumens/LPW (Delivered)130/17.1 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Input Frequency	60 Hz	
CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Lumens/LPW (Source)	623/69.2 (LM-82)	
CRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Lumens/LPW (Delivered)	130/17.1 (LM-79)	Glass Width: . Height:
Life (hours) 60,000 (L70/TM-21) FCC Meets FCC Title 47, Part 15 Class B Min. Start Temp30 °C Max. Operating Temp 30 °C Warranty 5 year warranty Labels cSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	ССТ	3000 K	
FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	CRI	90 CRI	
Min. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualifiedMeets California Title 24 high efficacy requirements	Life (hours)	60,000 (L70/TM-21)	
Max. Operating Temp 30 °C   Warranty 5 year warranty   Labels cCSAus Wet location listed   ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	FCC	Meets FCC Title 47, Part 15 Class B	
Warranty 5 year warranty   Labels cCSAus Wet location listed   ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Min. Start Temp	-30 °C	
Labels cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Max. Operating Temp	30 °C	
ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Warranty	5 year warranty	
Meets California Title 24 high efficacy requirements	Labels	cCSAus Wet location listed	
		ENERGY STAR <sup>®</sup> qualified	
for outdoor use only		Meets California Title 24 high efficacy requirements	
		for outdoor use only	





#### **Dimensions:**

Width: 7" Depth: 8-5/8" Height: 10-3/8" H/CTR: 3-1/8"

Glass Width: 4-5/8" Height: 5-7/8"



# Small Wall Lantern

Wall mounted • Wet location listed PROGRESS LED



# P6084-2030K9

### **Dimming Notes:**

P6084 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.