

## 12" LED Tape 3000K

Surface mounted • Damp location listed **PROGRESS LED**

### Description:

LED Tape provides lighting to enhance aesthetics while also aiding in tasks around the home. Common applications for LED tape include undercabinet lighting in kitchens to add illumination to work surfaces, highlighting back splashes in kitchens and bathrooms, and adding toe kick lighting at the bases of cabinets. LED Tape light offers dramatic and functional light. This 12" tape is 3000K and can be cut every 4 inches.

### Specifications:

- Unfinished (-000) (Unfinished)
- Silicone Construction
- Tape is fully enclosed in silicone
- Color Temperature 3000K
- 90 CRI, 50,000 hr life
- Measures 12 in L x 3/8 in W x 1/8 in ht
- 300 lumens per foot, consumes 4.2w per foot
- Field cuttable at every 4" to end of run
- Damp location listed
- Undercabinet mount
- 3M adhesive backing and mounting clips standard
- Dimmable with a wide variety of incandescent and ELV dimmers
- Meets California Title 24 JA8-2016
- Works well with 24v transformer (P700020/P700021/P700023)
- Dimmable to 10% brightness (See Dimming Notes)

### Performance:

Input Power	4.2w
Input Voltage	24 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	300/71.42857143 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
Warranty	5 Year Warranty
Labels	ETL Damp location listed

## P700008-000-30

### Images:



### Dimensions:

Width: 0-3/8"  
Length: 12"  
Height: 0-1/8"

**P700008-000-30****Dimming Notes:**

---

P700008 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron\_NTEVL-300

Lutron\_DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.