

Quadrant LED

 Ceiling or Flush Wall Mounted • Damp Location Listed **PROGRESS LED**

Description:

Quadrant LED Collection 2-Light Matte Black Frosted Glass Modern Wall Light

Specifications:

- Frosted Acrylic Cylindrical
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.5 in W., 5.5 in ht., 1.375 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied
- Americans With Disabilities Act (ADA) compliant

Performance:

Number of Modules	2Wall Bracket
Input Power	13 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	686/53 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed Meets California Title 24 JA8-2019

P710103-031-30



Dimensions:

Length: 8-1/16 in
Depth: 3.3 in
Height: 24 in

Frosted Acrylic Cylindrical
Width: 1-1/4 in
Height: 4-3/4 in

P710103-031-30

Dimming Notes:

P710103-031-30 is designed to be compatible with many ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.