

Project:

Fixture Type:

Location:

Contact:

Intrinsic

Recessed Mounted • Damp Location Listed



P800018-031-CS

Description:

Intrinsic Collection 6 " 5-CCT Black LED Eyeball Trim for Recessed Housings

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- 6 in of wire supplied

Performance:

Input Power	8 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	698/87 (LM-79)
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	ENERGY STAR [®] qualified
	Meets California Title 20



Dimensions:

Diameter: 7-11/16 in Height: 3-15/16 in



The adjustable light source can be aimed allowing the trim to be used as a standard downlight, accent light, wall wash or sloped ceiling light.



Intrinsic

Recessed Mounted • Damp Location Listed

PROGRESS LED

Photometrics:

ELECTRICAL DATA	P800018-031-CS	
Input Voltage	120 V	
Input Frequency	60 Hz	
THD	<20%	
EMI/RFI	FCC Title 47, Part 15, Class B	
Operating Temperature	-40 °C to 40 °C	
Dimming	Yes*	
*See Dimming Notes for more information		

P800018-031-CS



Intrinsic

Recessed Mounted • Damp Location Listed

PROGRESS LED

P800018-031-CS

Dimming Notes:

 $\mathsf{P800018}\text{-}\mathsf{O31}\text{-}\mathsf{CS}$ is designed to be compatible with many ELV/Reverse Phase Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Eaton AAL06	
Eaton SAL06P	
IDevices IDEV009	
Leviton 6681	
Leviton IP106-1LZ	
Leviton 6672	
Leviton 6674	
Lutron NTEVL-300	
Lutron DVELV-300P	
Lutron Caseta Wireless	
Lutron AYCL-153P	
Lutron SCL-153P	
Lutron TGCL-153-PH-WH	
Lutron MACL-153M	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.