

Project:

Fixture Type:

Location:

Contact:

Intrinsic

Recessed housing Mounted • Wet Location Listed PROGRESS LED



Description:

Intrinsic Collection 5" - 6" 1000 lumen LED Recessed Trim

Specifications:

- · Dimmable to 10% brightness (See Dimming Notes)
- 6 in of wire supplied
- · Americans With Disabilities Act (ADA) compliant

Performance:

Input Power	13 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,356/107 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Wet Location Listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2019

Meets California Title 20

P800021-028-30



Dimensions:

Diameter: 7-7/16 in Height: 3-3/8 in



Intrinsic

Recessed housing Mounted • Wet Location Listed PROGRESS LED





Dimming Notes:

P800021-028-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

P800021-028-30

Dimming Controls:

Lutron NTEVL-300

Lutron DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.