

Project:		
Fixture Type:		
Location:		

## Intrinsic

Recessed housing Mounted • Damp Location Listed PROGRESS LED

Contact:



## **Description:**

Intrinsic Collection 4" Adjustable Eyeball 5-CCT Recessed Trim

## **Specifications:**

- Dimmable to 10% brightness (See Dimming Notes)
- 6 in of wire supplied
- · Americans With Disabilities Act (ADA) compliant

#### **Performance:**

Number of Modules	1 Recessed	
Input Power	8 W	
Input Voltage	120 VAC	
Input Frequency	60 Hz	
Lumens/LPW (Delivered)	801/100 (LM-79)	
CCT	2700 K, 3000 K, 3500 K, 4000 K, 5000 K	
CRI	90 CRI	
Life (hours)	50000 (L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15, Class B	
Warranty	5-year Limited Warranty	
Labels	cCSAus Damp Location Listed	
	ENERGY STAR® qualified	
	Meets California Title 20	





## **Dimensions:**

Diameter: 5-11/16 in Height: 3-3/16 in



## **Intrinsic**

Recessed housing Mounted • Damp Location Listed PROGRESS LED



## **Dimming Notes:**

P800022-028-CS is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

# P800022-028-CS

## **Dimming Controls:**

Eaton AAL06 Eaton SAL06P IDevices IDEV009 Leviton 6681 Leviton IPI06-1LZ Leviton 6672 Leviton 6674 Lutron NTEVL-300 Lutron DVELV-300P Lutron AYCL-153P Lutron SCL-153P Lutron TGCL-153-PH-WH Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.