

**Description:**

Everlume Collection 1-Light Satin White Modern LED Linear Panel Light

**Specifications:**

- Dimmable to 10% brightness (See Dimming Notes)
- Mounting backplate for outlet box included
- 6 in of wire supplied

**Performance:**

|                        |   |
|------------------------|---|
| Number of Modules      | 1   |
| Input Power            | 20.6 W  |
| Input Voltage          | 120 VAC   |
| Input Frequency        | 60 Hz   |
| Lumens/LPW (Delivered) | 1,581/76 (LM-79)  |
| CCT                    | 3000 K  |
| CRI                    | 90 CRI  |
| Life (hours)           | 50000 (L70/TM-21)   |
| EMI/RFI                | FCC Title 47, Part 15, Class B  |
| Warranty               | 5-year Limited Warranty   |
| Labels                 | cCSAus Damp Location Listed<br>ENERGY STAR® qualified<br>Meets California Title 24 JA8-2016 |

# P810032-028-30



**Dimensions:**

Length: 11-15/16 in  
Depth: 23-3/4 in  
Height: 1-3/16 in

**Dimming Notes:**

---

P810032-028-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

Eaton AAL06

Leviton 6681

Leviton IPI06-1LZ

Leviton 6674

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

# P810032-028-30