

PEOEU SERIES

Decorative LED AC/Emergency Light

Specifications:

Description:

The PEOEU Series offers LED performance in “normally on” AC and emergency lighting modes. The unit has a prismatic polycarbonate refractor with a durable die-cast aluminum housing available with durable powder coated dark bronze finish. The housing is fully sealed and gasketed. It is designed for wall mounting with a universal K/O pattern in the back-plate for installation to most standard size junction boxes. Illumination is provided by 2 high power LEDs driven at 3 watts each. LED color at 5500K.

Features:

- LED life-cycle of more than 10 years
- Includes self-diagnostic feature to monitor proper operation
- Universal 100-300 VAC input
- Includes long-life 4.8 VDC Nickel Cadmium battery for UL recognized 90 minute operation
- Full re-charge within 24 hours
- Water-proof test switch and AC-On indicator
- Optional photo-cell for normally-on operation

Application:

The PEOEU Series can be applied in areas that are susceptible to rain and severe moisture, such as parking decks and outdoor commercial applications.

Input Power Requirements:

| | | 120V | | 277 V | |
|---------------|--------|---------|--------|---------|--------|
| PEOEU-EM | AC ON | 9.00 W | 0.13 A | 8.89 W | 0.07 A |
| | AC OFF | 2.04 W | 0.04 A | 2.15 W | 0.02 A |
| PEOEU-EM -HTR | AC ON | 18.47 W | 0.21A | 58.90 W | 0.25 A |
| | AC OFF | 11.51 W | 0.11 A | 52.15 W | 0.20 A |

Compliances:

- Listed to UL924 Wet Location
- NFPA 101 and NFPA 70
- OSHA


Catalog number:

| Base | Emergency | Finish | Option |
|--------------|-------------------------------|--------------------|---------------------|
| PEOEU | EM - Emergency Battery | 20 - Bronze | HTR - Heater |

Images:



Dimensions:



Warranty:

2 year full unit warranty