

Element square

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

UPGRADE



WET



LOW-GLARE



ENERGY STAR



IC

RATED




AIR TIGHT



CERTIFIED



Intertek



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
RGR2SQ-CC	2"	8 W	600 lm	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
RGR4SQ-CC	4"	14 W	1100 lm	1200 lm	90		120 V
RGR6SQ-CC	6"	20 W	1600 lm	1900 lm	90		120 V

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained
 Superior LED performance and lifespan
 Regressed light source
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 40° beam angle
 Suitable for wet locations
 JA8 Certified
 Refer to website for dimmer compatibility
 Ideal operating temperature: -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

Accessories

RFP-23
 Rough-in plate for RGR2SQ

RFP-46
 Rough-in plate for RGR4SQ & RGR6SQ

Order example

RGR2SQ-CC-SN
 Dimmable RGR2SQ-CC 2" square regressed LED fixture in a satin nickel finish

Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

