

Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
СОВТР1М	1m (39")	12 W	550 lm	90	3000 K	12 V
СОВТРЗМ	3m (118")	24 W	1500 lm	90	3000 K	12 V
СОВТР5М	5m (196")	48 W	2250 lm	90	3000 K	12 V
COBTP-REEL*	20m (65')	8 W /meter	500 lm /meter	90	3000 K	12 V
COBTP-REEL-4K*	20m (65')	8 W /meter	500 lm /meter	90	4000 K	12 V

^{*20}m COB reels do not include a 12V driver. Plug-in or hard-wired power supply required for installation. Sold separately.

Specifications

12V DC LED plug-in driver included (1m=12w / 3m=24w / 5m=48w)

Excellent color rendering

Seamless light emission (360 LEDs/meter)

Warm white light output

Superior LED performance and lifespan

Over 50,000 hours of service life

Can be cut at every cut mark (every 2cm)

Maximum run length of 5m (196") in a series

Dimmable with DALS dimming power supply and most low-voltage

electronic dimmers

Refer to website for dimmer compatibility

5-year warranty

Power supplies: plug-in

ETR-LED10WPI

12V DC/10W class 2 LED driver

ETR-LED24WPI

12V DC/24W class 2 LED driver

Power supplies: hard-wired

BT06DIM-IC

6W dimmable LED hardwire driver

BT12DIM-IC

12W dimmable LED hardwire driver

BT24DIM-IC

24W dimmable LED hardwire driver

RT36DIM

36W dimmable LED hardwire driver

BT48DIM

48W dimmable LED hardwire driver

Accessories

COBTP-ALXT-BK

1 meter black aluminum extrusion with black lens

COBTP-ALXT-WH

1 meter white aluminum extrusion with white lens

COBTP-ALXT-L5M-BK

5 meter black lens for extrusions

COBTP-ALXT-L5M-WH

5 meter white lens for extrusions

COBTP-EXT02

2" extension with reconnect connectors

COBTP-EXT24

24" extension with reconnect connectors

COBTP-EXT60

60" extension with reconnect connectors

COBTP-CC06

Connection cord for hard-wired driver installation

СОВТР1М	1 x 1m
СОВТРЗМ	1 x 3m
СОВТР5М	1 x 5m
COBTP-REEL*	1 x 20m (65')

^{*} Driver not included



